

SQL: Queries, Constraints, Triggers

Chapter 5

Example Instances

R1	sid	bid	day
	22	101	10/10/96
	58	103	11/12/96

❖ We will use these instances of the Sailors and Reserves relations in our examples.

❖ If the key for the Reserves relation contained only the attributes *sid* and *bid*, how would the semantics differ?

S1	sid	sname	rating	age
	22	dustin	7	45.0
	31	lubber	8	55.5
	58	rusty	10	35.0

S2	sid	sname	rating	age
	28	yuppy	9	35.0
	31	lubber	8	55.5
	44	guppy	5	35.0
	58	rusty	10	35.0

Basic SQL Query

```
SELECT [DISTINCT] target-list
FROM relation-list
WHERE qualification
```

- ❖ **relation-list** A list of relation names (possibly with a *range-variable* after each name).
- ❖ **target-list** A list of attributes of relations in *relation-list*
- ❖ **qualification** Comparisons (Attr *op* const or Attr1 *op* Attr2, where *op* is one of <, >, =, ≤, ≥, ≠) combined using AND, OR and NOT.
- ❖ **DISTINCT** is an optional keyword indicating that the answer should not contain duplicates. Default is that duplicates are not eliminated!

Conceptual Evaluation Strategy

- ❖ Semantics of an SQL query defined in terms of the following conceptual evaluation strategy:
 - Compute the cross-product of *relation-list*.
 - Discard resulting tuples if they fail *qualifications*.
 - Delete attributes that are not in *target-list*.
 - If **DISTINCT** is specified, eliminate duplicate rows.
- ❖ This strategy is probably the least efficient way to compute a query! An optimizer will find more efficient strategies to compute *the same answers*.

Example of Conceptual Evaluation

```
SELECT S.sname
FROM Sailors S, Reserves R
WHERE S.sid=R.sid AND R.bid=103
```

(sid)	sname	rating	age	(sid)	bid	day
22	dustin	7	45.0	22	101	10/10/96
22	dustin	7	45.0	58	103	11/12/96
31	lubber	8	55.5	22	101	10/10/96
31	lubber	8	55.5	58	103	11/12/96
58	rusty	10	35.0	22	101	10/10/96
58	rusty	10	35.0	58	103	11/12/96

A Note on Range Variables

- ❖ Really needed only if the same relation appears twice in the FROM clause. The previous query can also be written as:

```
SELECT S.sname
FROM Sailors S, Reserves R
WHERE S.sid=R.sid AND bid=103

OR

SELECT sname
FROM Sailors, Reserves
WHERE Sailors.sid=Reserves.sid
AND bid=103
```

It is good style, however, to use range variables always!

Find sailors who've reserved at least one boat

```
SELECT S.sid
FROM Sailors S, Reserves R
WHERE S.sid=R.sid
```

- ❖ Would adding DISTINCT to this query make a difference?
- ❖ What is the effect of replacing S.sid by S.sname in the SELECT clause? Would adding DISTINCT to this variant of the query make a difference?

Expressions and Strings

```
SELECT S.age, age1=S.age-5, 2*S.age AS age2
FROM Sailors S
WHERE S.sname LIKE 'B_%B'
```

- ❖ Illustrates use of arithmetic expressions and string pattern matching: Find triples (of ages of sailors and two fields defined by expressions) for sailors whose names begin and end with B and contain at least three characters.
- ❖ AS and = are two ways to name fields in result.
- ❖ LIKE is used for string matching. `_` stands for any one character and `%` stands for 0 or more arbitrary characters.

Find sid's of sailors who've reserved a red or a green boat

- ❖ UNION: Can be used to compute the union of any two *union-compatible* sets of tuples (which are themselves the result of SQL queries).
- ❖ If we replace OR by AND in the first version, what do we get?
- ❖ Also available: EXCEPT (What do we get if we replace UNION by EXCEPT?)

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
AND (B.color='red' OR B.color='green')
```

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
AND B.color='red'
```

```
UNION
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
AND B.color='green'
```

Find sid's of sailors who've reserved a red and a green boat

- ❖ INTERSECT: Can be used to compute the intersection of any two *union-compatible* sets of tuples.
- ❖ Included in the SQL/92 standard, but some systems don't support it.
- ❖ Contrast symmetry of the UNION and INTERSECT queries with how much the other versions differ.

```
SELECT S.sid
FROM Sailors S, Boats B1, Reserves R1,
Boats B2, Reserves R2
WHERE S.sid=R1.sid AND R1.bid=B1.bid
AND S.sid=R2.sid AND R2.bid=B2.bid
AND (B1.color='red' AND B2.color='green')
```

```
SELECT S.sid Key field!
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
AND B.color='red'
```

```
INTERSECT
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
AND B.color='green'
```

Nested Queries

Find names of sailors who've reserved boat #103:

```
SELECT S.sname
FROM Sailors S
WHERE S.sid IN (SELECT R.sid
FROM Reserves R
WHERE R.bid=103)
```

- ❖ A very powerful feature of SQL: a WHERE clause can itself contain an SQL query! (Actually, so can FROM and HAVING clauses.)
- ❖ To find sailors who've *not* reserved #103, use NOT IN.
- ❖ To understand semantics of nested queries, think of a *nested loops* evaluation: For each Sailors tuple, check the qualification by computing the subquery.

Nested Queries with Correlation

Find names of sailors who've reserved boat #103:

```
SELECT S.sname
FROM Sailors S
WHERE EXISTS (SELECT *
FROM Reserves R
WHERE R.bid=103 AND S.sid=R.sid)
```

- ❖ EXISTS is another set comparison operator, like IN.
- ❖ If UNIQUE is used, and * is replaced by R.bid, finds sailors with at most one reservation for boat #103. (UNIQUE checks for duplicate tuples; * denotes all attributes. Why do we have to replace * by R.bid?)
- ❖ Illustrates why, in general, subquery must be re-computed for each Sailors tuple.

More on Set-Comparison Operators

- ❖ We've already seen IN, EXISTS and UNIQUE. Can also use **NOT IN, NOT EXISTS** and **NOT UNIQUE**.
- ❖ Also available: *op ANY, op ALL, op IN* >, <, =, ≥, ≤, ≠
- ❖ Find sailors whose rating is greater than that of some sailor called Horatio:

```
SELECT *
FROM Sailors S
WHERE S.rating > ANY (SELECT S2.rating
                     FROM Sailors S2
                     WHERE S2.sname='Horatio')
```

Rewriting INTERSECT Queries Using IN

Find sid's of sailors who've reserved both a red and a green boat:

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid AND B.color='red'
AND S.sid IN (SELECT S2.sid
             FROM Sailors S2, Boats B2, Reserves R2
             WHERE S2.sid=R2.sid AND R2.bid=B2.bid
             AND B2.color='green')
```

- ❖ Similarly, EXCEPT queries re-written using NOT IN.
- ❖ To find *names* (not *sid*'s) of Sailors who've reserved both red and green boats, just replace *S.sid* by *S.sname* in SELECT clause. (What about INTERSECT query?)

Division in SQL

Find sailors who've reserved all boats.

- ❖ Let's do it the hard way, without EXCEPT:

```
(1) SELECT S.sname
     FROM Sailors S
     WHERE NOT EXISTS
           ((SELECT B.bid
            FROM Boats B)
          EXCEPT
          (SELECT R.bid
           FROM Reserves R
           WHERE R.sid=S.sid))

(2) SELECT S.sname
     FROM Sailors S
     WHERE NOT EXISTS (SELECT B.bid
                      FROM Boats B
                      WHERE NOT EXISTS (SELECT R.bid
                                       FROM Reserves R
                                       WHERE R.bid=B.bid
                                       AND R.sid=S.sid))

Sailors S such that ...
    there is no boat B without ...
        a Reserves tuple showing S reserved B
```

Aggregate Operators

- ❖ Significant extension of relational algebra.

```
COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)
```

single column

```
SELECT COUNT (*)
FROM Sailors S

SELECT AVG (S.age)
FROM Sailors S
WHERE S.rating=10

SELECT COUNT (DISTINCT S.rating)
FROM Sailors S
WHERE S.sname='Bob'

SELECT S.sname
FROM Sailors S
WHERE S.rating= (SELECT MAX(S2.rating)
                FROM Sailors S2)

SELECT AVG (DISTINCT S.age)
FROM Sailors S
WHERE S.rating=10
```

Find name and age of the oldest sailor(s)

- ❖ The first query is illegal! (We'll look into the reason a bit later, when we discuss **GROUP BY**.)
- ❖ The third query is equivalent to the second query, and is allowed in the SQL/92 standard, but is not supported in some systems.

```
SELECT S.sname, MAX (S.age)
FROM Sailors S

SELECT S.sname, S.age
FROM Sailors S
WHERE S.age =
      (SELECT MAX (S2.age)
       FROM Sailors S2)

SELECT S.sname, S.age
FROM Sailors S
WHERE (SELECT MAX (S2.age)
       FROM Sailors S2)
      = S.age
```

Motivation for Grouping

- ❖ So far, we've applied aggregate operators to all (qualifying) tuples. Sometimes, we want to apply them to each of several *groups* of tuples.
- ❖ Consider: *Find the age of the youngest sailor for each rating level.*
 - In general, we don't know how many rating levels exist, and what the rating values for these levels are!
 - Suppose we know that rating values go from 1 to 10; we can write 10 queries that look like this (!):

```
For i = 1, 2, ..., 10:
    SELECT MIN (S.age)
    FROM Sailors S
    WHERE S.rating = i
```

Queries With GROUP BY and HAVING

```
SELECT [DISTINCT] target-list
FROM relation-list
WHERE qualification
GROUP BY grouping-list
HAVING group-qualification
```

- ❖ The *target-list* contains (i) **attribute names** (ii) terms with aggregate operations (e.g., MIN (S.age)).
 - The **attribute list (i)** must be a subset of *grouping-list*. Intuitively, each answer tuple corresponds to a *group*, and these attributes must have a single value per group. (A *group* is a set of tuples that have the same value for all attributes in *grouping-list*.)

Conceptual Evaluation

- ❖ The cross-product of *relation-list* is computed, tuples that fail *qualification* are discarded, 'unnecessary' fields are deleted, and the remaining tuples are partitioned into groups by the value of attributes in *grouping-list*.
- ❖ The *group-qualification* is then applied to eliminate some groups. Expressions in *group-qualification* must have a **single value per group!**
 - In effect, an attribute in *group-qualification* that is not an argument of an aggregate op also appears in *grouping-list*. (SQL does not exploit primary key semantics here!)
- ❖ One answer tuple is generated per qualifying group.

Find age of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors

```
SELECT S.rating, MIN (S.age)
      AS minage
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT (*) > 1
```

Answer relation:

rating	minage
3	25.5
7	35.0
8	25.5

Sailors instance:

sid	sname	rating	age
22	dustin	7	45.0
29	brutus	1	33.0
31	lubber	8	55.5
32	andy	8	25.5
58	rusty	10	35.0
64	horatio	7	35.0
71	zorba	10	16.0
74	horatio	9	35.0
85	art	3	25.5
95	bob	3	63.5
96	frodo	3	25.5

Find age of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors.

rating	age
7	45.0
1	33.0
8	55.5
8	25.5
10	35.0
7	35.0
10	16.0
9	35.0
3	25.5
3	63.5
3	25.5

→

rating	age
1	33.0
3	25.5
3	63.5
3	25.5
7	45.0
7	35.0
8	55.5
8	25.5
9	35.0
10	35.0

→

rating	minage
3	25.5
7	35.0
8	25.5

Find age of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors and with every sailor under 60.

HAVING COUNT (*) > 1 AND EVERY (S.age <= 60)

rating	age
7	45.0
1	33.0
8	55.5
8	25.5
10	35.0
7	35.0
10	16.0
9	35.0
3	25.5
3	63.5
3	25.5

→

rating	age
1	33.0
3	25.5
3	63.5
3	25.5
7	45.0
7	35.0
8	55.5
8	25.5
9	35.0
10	35.0

→

rating	minage
7	35.0
8	25.5

What is the result of changing EVERY to ANY?

Find age of the youngest sailor with age ≥ 18 , for each rating with at least 2 sailors between 18 and 60.

```
SELECT S.rating, MIN (S.age)
      AS minage
FROM Sailors S
WHERE S.age >= 18 AND S.age <= 60
GROUP BY S.rating
HAVING COUNT (*) > 1
```

Answer relation:

rating	minage
3	25.5
7	35.0
8	25.5

Sailors instance:

sid	sname	rating	age
22	dustin	7	45.0
29	brutus	1	33.0
31	lubber	8	55.5
32	andy	8	25.5
58	rusty	10	35.0
64	horatio	7	35.0
71	zorba	10	16.0
74	horatio	9	35.0
85	art	3	25.5
95	bob	3	63.5
96	frodo	3	25.5

For each red boat, find the number of reservations for this boat

```
SELECT B.bid, COUNT (*) AS scout
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid AND B.color='red'
GROUP BY B.bid
```

- ❖ Grouping over a join of three relations.
- ❖ What do we get if we remove *B.color='red'* from the WHERE clause and add a HAVING clause with this condition?
- ❖ What if we drop Sailors and the condition involving S.sid?

Find age of the youngest sailor with age > 18, for each rating with at least 2 sailors (of any age)

```
SELECT S.rating, MIN (S.age)
FROM Sailors S
WHERE S.age > 18
GROUP BY S.rating
HAVING 1 < (SELECT COUNT (*)
FROM Sailors S2
WHERE S.rating=S2.rating)
```

- ❖ Shows HAVING clause can also contain a subquery.
- ❖ Compare this with the query where we considered only ratings with 2 sailors over 18!
- ❖ What if HAVING clause is replaced by:
 - HAVING COUNT(*) >1

Find those ratings for which the average age is the minimum over all ratings

- ❖ Aggregate operations cannot be nested! **WRONG:**

```
SELECT S.rating
FROM Sailors S
WHERE S.age = (SELECT MIN (AVG (S2.age)) FROM Sailors S2)
```

- ❖ Correct solution (in SQL/92):

```
SELECT Temp.rating, Temp.avgage
FROM (SELECT S.rating, AVG (S.age) AS avgage
FROM Sailors S
GROUP BY S.rating) AS Temp
WHERE Temp.avgage = (SELECT MIN (Temp.avgage)
FROM Temp)
```

Null Values

- ❖ Field values in a tuple are sometimes *unknown* (e.g., a rating has not been assigned) or *inapplicable* (e.g., no spouse's name).
 - SQL provides a special value *null* for such situations.
- ❖ The presence of *null* complicates many issues. E.g.:
 - Special operators needed to check if value is/is not *null*.
 - Is *rating>8* true or false when *rating* is equal to *null*? What about **AND**, **OR** and **NOT** connectives?
 - We need a **3-valued logic** (true, false and *unknown*).
 - Meaning of constructs must be defined carefully. (e.g., WHERE clause eliminates rows that don't evaluate to true.)
 - New operators (in particular, *outer joins*) possible/needed.

Integrity Constraints (Review)

- ❖ An IC describes conditions that every *legal instance* of a relation must satisfy.
 - Inserts/deletes/updates that violate IC's are disallowed.
 - Can be used to ensure application semantics (e.g., *sid* is a key), or prevent inconsistencies (e.g., *sname* has to be a string, *age* must be < 200)
- ❖ **Types of IC's:** Domain constraints, primary key constraints, foreign key constraints, general constraints.
 - **Domain constraints:** Field values must be of right type. Always enforced.

General Constraints

```
CREATE TABLE Sailors
(sid INTEGER,
sname CHAR(10),
rating INTEGER,
age REAL,
PRIMARY KEY (sid),
CHECK (rating >= 1
AND rating <= 10))

CREATE TABLE Reserves
(sname CHAR(10),
bid INTEGER,
day DATE,
PRIMARY KEY (bid,day),
CONSTRAINT noInterlakeRes
CHECK ('Interlake' <>
(SELECT B.bname
FROM Boats B
WHERE B.bid=bid)))
```

- ❖ Useful when more general ICs than keys are involved.
- ❖ Can use queries to express constraint.
- ❖ Constraints can be named.

Constraints Over Multiple Relations

```
CREATE TABLE Sailors
  ( sid INTEGER,
    sname CHAR(10),
    rating INTEGER,
    age REAL,
    PRIMARY KEY (sid),
    CHECK
    ( (SELECT COUNT (S.sid) FROM Sailors S)
      + (SELECT COUNT (B.bid) FROM Boats B) < 100
    )
  )
```

Number of boats plus number of sailors is < 100

- ❖ Awkward and wrong!
- ❖ If Sailors is empty, the number of Boats tuples can be anything!
- ❖ ASSERTION is the right solution; not associated with either table.

```
CREATE ASSERTION smallClub
CHECK
( (SELECT COUNT (S.sid) FROM Sailors S)
  + (SELECT COUNT (B.bid) FROM Boats B) < 100
)
```

Triggers

- ❖ Trigger: procedure that starts automatically if specified changes occur to the DBMS
- ❖ Three parts:
 - Event (activates the trigger)
 - Condition (tests whether the triggers should run)
 - Action (what happens if the trigger runs)

Triggers: Example (SQL:1999)

```
CREATE TRIGGER youngSailorUpdate
AFTER INSERT ON SAILORS
REFERENCING NEW TABLE NewSailors
FOR EACH STATEMENT
INSERT
  INTO YoungSailors(sid, name, age, rating)
  SELECT sid, name, age, rating
  FROM NewSailors N
  WHERE N.age <= 18
```

Summary

- ❖ SQL was an important factor in the early acceptance of the relational model; more natural than earlier, procedural query languages.
- ❖ Relationally complete; in fact, significantly more expressive power than relational algebra.
- ❖ Even queries that can be expressed in RA can often be expressed more naturally in SQL.
- ❖ Many alternative ways to write a query; optimizer should look for most efficient evaluation plan.
 - In practice, users need to be aware of how queries are optimized and evaluated for best results.

Summary (Contd.)

- ❖ NULL for unknown field values brings many complications
- ❖ SQL allows specification of rich integrity constraints
- ❖ Triggers respond to changes in the database